

# Vertical Press Brakes – BP-5060NC



SPECIFICATIONS – BP-5060NC		
Maximum Pressure	50 tons	45 ton
Bending Capacity (max. length @ max. thickness)	61" / .118"	1550 mm / 3 mm
Distance Between Housings	49.21"	1250 mm
Distance From Table to Ram	11.81"	300 mm
Throat Depth (to housing)	7.87"	200 mm
Stroke Distance	5.9"	150 mm
Approach Speed	3.14" / sec.	
Bending Speed	.275" / sec.	
Return Speed	2.36" / sec.	
Power Back Gauge Length	23.62"	600 mm
Main Motor	5 hp	
Back Gauge Motor	1/2 hp	
Voltage	220V / 3-phase	
Oil Capacity	28 gal.	
Shipping Dimensions (L x W x H)	74.80"x51.18"x86.61"	1900x1300x2200mm
Shipping Weight	6,160 lbs.	2800 kgs.

*Specifications subject to change without notice.*

- ◆ Electric back gauge with manual micrometer adjustment standard
- ◆ Extra-wide guideways for exceptional rigidity
- ◆ Adjustable 2-step downward travel for higher productivity
- ◆ Oversized hydraulic tank with high-performance pump smooths and stabilizes oil flow
- ◆ Photo electric safety curtain standard
- ◆ Vertical positioning via electronic encoder and mechanical stops