

## CS-315EU

- ◆ 12.5" blade
- ◆ Manual feed
- ◆ Miters up to 45° left and right
- ◆ 220V, 1-phase



**HEAVY DUTY  
CONSTRUCTION**

## CS-350EU

- ◆ 14" blade
- ◆ Variable speed inverter driven
- ◆ Digital readout for rpm
- ◆ Miters 45° left and right
- ◆ 220V, 1-phase



CS-315EU		
Mitering Capacities	90°	45°
○	4" (100 mm)	4" (100 mm)
●	2" (50 mm)	2" (50 mm)
□	3.2" x 3.2" (82 mm x 82 mm)	3.2" x 3.2" (82 mm x 82 mm)
▣	4.25" x 2.75" (110 mm x 70 mm)	3.25" x 2.75" (85 mm x 70 mm)
Specifications		
Maximum Blade Diameter	12.5" (317 mm)	
Arbor Size	1.26" (32 mm)	
Blade Speed	52 rpm	
Operation	Manual	
Head Style	Pivot	
Maximum Vise Opening	4.72" (120 mm)	
Vise Style	Single Action with Cam Lock	
Head Miter	45° Left / 45° Right	
Slotting Capable	No	
Coolant System	Yes	
Motor	2.5 hp	
Electrical Requirements	220V, 1-Phase	
Shipping Dimensions (L x W x H)	40" x 40" x 72" (1016 x 1016 x 1829 mm)	
Shipping Weight	500 lbs. (228 kgs.)	

CS-350EU		
Mitering Capacities	90°	45°
○	4.7" (120 mm)	4" (100 mm)
●	3.5" (90 mm)	3" (75 mm)
□	4" x 4" (100 mm x 100 mm)	3.5" x 3.5" (90 mm x 90 mm)
▣	6.3" x 3.5" (160 mm x 90 mm)	3.5" x 2.8" (90 mm x 70 mm)
Specifications		
Maximum Blade Diameter	14" (350 mm)	
Arbor Size	1.26" (32 mm)	
Blade Speed	24 – 120 rpm	
Operation	Manual	
Head Style	Pivot	
Maximum Vise Opening	4.7" (120 mm)	
Vise Style	Single Action with Cam Lock	
Head Miter	45° Left / 45° Right	
Slotting Capable	No	
Coolant System	Yes	
Motor	3 hp	
Electrical Requirements	220V, 1-Phase	
Shipping Dimensions (L x W x H)	60" x 44" x 48" (1524 x 1118 x 1219 mm)	
Shipping Weight	550 lbs. (250 kgs.)	