

Hydraulic Shears – SH-5203-HD / SH-5203-HD-NC

SPECIFICATIONS SH-5203-HD		
Shear Length	52"	1321 mm
Thickness (SS)	1/4" (7 ga.)	
Minimum Thickness	24 ga.	
Front Gauge Length	39.37"	1000 mm
Back Gauge Length	23.62"	600 mm
Strokes per Minute	16 – 24	
Blade Angle	1/2° – 2° Adjustable	
Motor	15 hp	
Power Requirements	220V 3-Phase	
Shipping Dimensions (L x W x H)	91" x 54" x 65"	2311 x 1372 x 1651 mm
Shipping Weight	5,720 lbs.	2600 kgs.

Specifications subject to change without notice.

- ◆ 52" x 1/4"-mild steel capacity
- ◆ Front and back gauges
- ◆ Fast blade gap adjustment
- ◆ 4 sided blades ◆ 220V 3-phase



SH-5203-HD

- ◆ 52" x 1/4"-mild steel capacity
- ◆ NC back gauge
- ◆ Minkol controller
- ◆ Front material guides
- ◆ Fast blade gap adjustment
- ◆ Shadow line for material placement
- ◆ 4 sided blades
- ◆ 220V 3-phase

SPECIFICATIONS SH-5203-HD-NC		
Shear Length	52"	1321 mm
Thickness (SS)	1/4" (7 ga.)	
Minimum Thickness	24 ga.	
Front Gauge Length	39.37"	1000 mm
Back Gauge Length	23.62"	600 mm
Strokes per Minute	16 – 24	
Blade Angle	1/2° – 2° Adjustable	
Motor	15 hp	
Power Requirements	220V 3-Phase	
Shipping Dimensions (L x W x H)	91" x 54" x 65"	2311 x 1372 x 1651 mm
Shipping Weight	5,720 lbs.	2600 kgs.

Specifications subject to change without notice.



SH-5203-HD-NC