

Hydraulic Shears – SH-8014 / SH-8010

SPECIFICATIONS – SH-8014		
Shear Length	80"	2032 mm
Thickness (SS)	14 ga. (18 ga.)	
Minimum Thickness	24 ga.	
Front Gauge Length	24"	609 mm
Back Gauge Length	24"	609 mm
Strokes per Minute	26	
Blade Angle	1°	
Motor	3 hp	
Power Requirements	220V 3-phase	
Shipping Dimensions (L x W x H)	104" x 36" x 53"	2642 x 914 x 1346 mm
Shipping Weight	3,700 lbs.	1682 kgs.

Specifications subject to change without notice.

- ◆ 80" x 14-gauge mild steel capacity
- ◆ High-carbon, high-chromium blades
- ◆ Front and back gauges
- ◆ 3 HP motor
- ◆ Front support arms with squaring bar
- ◆ Automatic and single-stroke operations with jog mode
- ◆ 26 strokes per minute
- ◆ Multi-sided blades
- ◆ 220V 3-phase

- ◆ 80" 10-gauge mild steel capacity
- ◆ High-carbon, high-chromium blades
- ◆ Front and back gauges
- ◆ 5 HP motor
- ◆ Front support arms with squaring bar
- ◆ Automatic and single-stroke operations with jog mode
- ◆ 24 strokes per minute
- ◆ Multi-sided blades
- ◆ 220V 3-phase

SPECIFICATIONS – SH-8010		
Shear Length	80"	2032 mm
Thickness (SS)	10 ga.	
Minimum Thickness	24 ga.	
Front Gauge Length	24"	609 mm
Back Gauge Length	24"	609 mm
Strokes per Minute	24	
Blade Angle	1°	
Motor	5 hp	
Power Requirements	220V 3-phase	
Shipping Dimensions (L x W x H)	104" x 36" x 53"	2642 x 914 x 1346 mm
Shipping Weight	4,000 lbs.	1818 kgs.

Specifications subject to change without notice.

