# 50 TON



SPECIFICATIONS		
Punch Rating (tons)	50	
Punch Max Capacity (In.)	1 diam. in 5/8 mild steel	
Punch Work Height (In.)	39-9/16	
Punch Throat Depth (In.)	7	
Punch Stroke (In.)	1-7/8	
Flat Bar Shear Max Capacity (In.)	1/2 x 10 3/4 x 4	
Flat Bar Shear Work Height (In.)	34-1/2	
Flat Bar Shear Max Round Capacity (In.)	3/4 diam.	
Flat Bar Shear Max Square Capacity (In.)	3/4	
Angle Shear Max Capacity (In.)	3 x 3 x 3/8 4 x 4 x 1/4	
Angle Shear Work Height (In.)	39-7/8	
Coper Notcher Max Capacity (In.)	2 x 3 x 5/16	
Coper Notcher Work Height (In.)	39-1/2	
Motor	5 HP	
Amps	23	
Hydraulics (GPM)	3-1/2	
Hydraulics (PSI)	2500	
Hydraulic Reservoir (gal.)	7	
Product Dimensions (In.)	36-3/4 x 36-1/8 x 54-1/2	
Shipping Dimensions (In.)	45 x 51 x 62	
Weight (lbs.)	2,020	

### **FLEXIBILITY**

- Four workstations:
- Standard (4) Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- 9 interchangeable Attachments available to tailor the Ironworker to your needs
- 16 optional Accessories available to increase precision and efficiency

### **PRODUCTIVITY**

- · Compact machine that allows for fast and easy transitions between fabrication operations: punch, shear, notch, bend and cope all in one machine.
- · Optimized workstation heights for improved efficiency
- Electric foot pedal with integrated jog control
- Adjustable electric stoke control

### **SAFETY**

- · Bright LED lights increase visibility
- ANSI B11.5-1988(02) Compliant Guarding
- ETL Certified Controls
- Integrated Lock-out/Tag-out system with E-Stop for added safety

## **PERFORMANCE**

- Durable, heavy-duty, Made In USA steel construction
- Vertical movement produces even pressure resulting in precise punching and shearing with minimal distortion that results in extended tooling life
- Punches are easily changeable, long-lasting and available from 1/8" to 4" diameters along with square, oblong, hex, metric, and custom shapes
- Flat Bar Shear blades are made of precision machined, high-quality tool steel with 4 cutting edges for extended life
- · Angle Shear blades have 2 corner radii for both thin and thick material and are made of precision tool steel with 2 cutting edges for extended life

STOCK #	PRODUCT DESCRIPTION
IW50-1P230	50 Ton Ironworker 1 Phase, 230 Volt
IW50-3P208	50 Ton Ironworker 3 Phase, 208 Volt
IW50-3P230	50 Ton Ironworker 3 Phase, 230 Volt
IW50-3P380	50 Ton Ironworker Int'l - 3 Phase, 380 Volt, 50 Hz
IW50-3P460	50 Ton Ironworker 3 Phase, 460 Volt
IW50-3P575	50 Ton Ironworker 3 Phase, 575 Volt

# 50 TON WITH FOWER LINK





# 50 TON ATTACHMENTS



### OVERSIZE PLINCH ASSEMBLY

- · Accommodates punch & die sets in various shapes and
- Replaces Standard Punch Assembly or can be used as a secondary Punch Workstation

AC1024\*



### 241 PUNCH ASSEMBLY

- · Accommodates punch & die sets in various shapes and sizes from 1" up to 4"
- Punch large holes and slots n anything from heavy sheet metal to steel beams

AC1055\*



### ANGLE NOTCHER

- Take precise 92° notch out of mild steel up to 3" x 3" x 1/4"
- Allows for an easy 90° to create a steel frame

AC0125-1\*



- Make clean 90° saddle joint connections quickly and easily
- Compatible with all Edwards
- Contact Edwards for custom dies to match your project
- Pipe Notcher Dies sold

separately

AC0925\*



- Make clean 90° saddle joint connections quickly and easily
- Compatible with all Edwards Ironworkers
- Contact Edwards for custom
- dies to match your project Pipe Notcher Dies sold

separately AC0925T\*



- Designed to shear flat bar up to 1/4" x 6" and angle iron up to 2" x 2" x 1/4"
- Shears solid round bar 1/4", 3/8", 1/2", 3/4" and 13/16" square bar

AC1075\*



### ROD SHEAR

- Shear solid round rod easily with the Rod Shear
- Handles 1/4", 3/8", 1/2" 5/8" 3/4" and 1" solid

AC1074\*



## **BRAKE WITH 4-WAY DIE**

- Choose from the sizes listed below to meet your specific needs
- Fabricate brackets, frames, pans and tanks with this Brake with 4-Way Die
- Includes a standard punch that allows 1/16", 1/8", 3/16" and 1/4" material to be formed to a 90° angle

AC1033 AC1034\*

# 50 TON ACCESSORIES



### GAUGING TABLE KIT

- 3/8" thick 12" x 16" table that
- Compatible with both Standard and Oversize Pedestal Die Table
- Adjustable fences and handles quickly and easily guide your material for perfect repeatable actions



# HEAVY DUTY GAUGING

- 1" x 12" x 16" table adds speed and precision to your Punch Workstation
- Replaces Standard Pedestal Die Table
- Adjustable fences and handles quickly and easily guide your material for perfect repeatabl



# HEAVY DUTY GAUGING TABLE KIT FOR OVERSIZED PUNCH ASSEMBLY

- 1" x 12" x 16" table adds speed and precision to your Punch
- Workstation Replaces installed Die Table
- Adjustable fences and handles quickly and easily guide your material for perfect repeatable



### STRIPPER REDUCING PLATE

Designed to minimize distortion on thinner gauge materials when using 1/2" punches & dies set or smaller

AC1914-3



### URETHANE STRIPPER

 Minimize material distortion when working with light gauge material

AC1099



## OUICK CHANGE PUNCH ASSEMBLY

- Increase your efficiency by saving time and money with saving time and money w the Quick Change Punch Assembly.
- · Accepts both Standard and Oversize Punch & Die Sets

AC1001



## AUTO CUT - 48"

- Optimize your productivity or both the Flat Bar Shear and Angle Shear Workstations on your Edwards Ironworker
- The adjustable proximity sensor automatically cycles your Ironworker as you feed in material

AC1010



## BACK GAUGE - 48"

- Speed up production on repeatable cuts by providing an adjustable stop for the Flat Bar Shear and Angle Shear
- A positive stop attachment that is fitted to the back of the shearing

AC1011



# PRESS BRAKE BACK GAUGE

- Speed up production on repeatable bends by providing an adjustable stop for the various size Brake Attachments
- A positive stop attachment that is fitted to the back of the Ironworker ensures accurate bending

PR135



## PUNCH & DIE STARTER SET

- Includes 8 standard round punch & die sets selected
- Sized in 1/8" increments fron 3/16" to 1-1/16" with 1/32" clearance
- See catalog page 68-71 for PD1000



### ACCESSORY LIGHT

- Super bright LED light with M12 connections plugs
- Powerful magnetic base light to any Ironworker surface and move as needed

AC1000



# FABRICATOR'S PROTRACTOR

- Increase user accuracy on the Punch and Flat Bar Shear Workstations
- Designed to guide your workpiece and gauged at 15° increments through 180°



### 12" & 18" FENCES GUIDES

- Easily adjustable to align material, these 12" or 18" fence guides make precise.
- AC1910 12" Standard Handle AC1911 18" Standard Handle AC1912 12" Heavy Duty Handle: AC1913 18" Heavy Duty Handles



# PRODUCTIVITY PACK

- ncludes 5 Accessories designed o increase your accuracy and production speed.
- Accessory light 48" Auto Cut
- Fabricator's Protractor 3/8" x 12" x 16" Punch Station table Punch & Die Starter Kit

\*IMAGE NOTE: Guarding removed for clarity

\*IMAGE NOTE: Guarding removed for clarity

