60 TON





SPECIFICATIONS	
Punch Rating (tons)	60
Punch Max Capacity (In.)	1 diam. In 3/4 mild steel
Punch Work Height (In.)	36-9/16
Punch Throat Depth (In.)	8-7/8
Punch Stroke (In.)	1-1/4
Flat Bar Shear Max Capacity (In.)	3/8 x 14 1/2 x 12 3/4 x 4
Flat Bar Shear Work Height (In.)	34-1/2
Flat Bar Shear Max Round Capacity (In.)	7/8 diam.
Flat Bar Shear Max Square Capacity (In.)	7/8
Angle Shear Max Capacity (In.)	3 x 3 x 1/2 4 x 4 x 3/8
Angle Shear Work Height (In.)	39-7/8
Coper Notcher Max Capacity (In.)	2-1/2 x 4 x 5/16
Coper Notcher Work Height (In.)	39-1/2
Motor	5 HP
Amps	23
Hydraulics (GPM)	3-1/2
Hydraulics (PSI)	2500
Hydraulic Reservoir (gal.)	7
Product Dimensions (In.)	36-1/8 x 46-1/8 x 56-1/8
Shipping Dimensions (In.)	45 x 51 x 63
Weight (lbs.)	2,550

FLEXIBILITY

- Four workstations:
- Standard (4) Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- 9 interchangeable Attachments available to tailor the Ironworker to your needs
- 17 optional Accessories available to increase precision and efficiency

PRODUCTIVITY

- · Compact machine that allows for fast and easy transitions between fabrication operations: punch, shear, notch, bend and cope all in one machine.
- · Optimized workstation heights for improved efficiency
- Electric foot pedal with integrated jog control
- Adjustable electric stoke control

SAFETY

- · Bright LED lights increase visibility
- ANSI B11.5-1988(02) Compliant Guarding
- ETL Certified Controls
- Integrated Lock-out/Tag-out system with E-Stop for added safety

PERFORMANCE

- Durable, heavy-duty, Made In USA steel construction
- Vertical movement produces even pressure resulting in precise punching and shearing with minimal distortion that results in extended tooling life
- Punches are easily changeable, long-lasting and available from 1/8" to 4" diameters along with square, oblong, hex, metric, and custom shapes
- Flat Bar Shear blades are made of precision machined, high-quality tool steel with 4 cutting edges for extended life
- · Angle Shear blades have 2 corner radii for both thin and thick material and are made of precision tool steel with 2 cutting edges for extended life

STOCK #	PRODUCT DESCRIPTION
IW60-1P230	60 Ton Ironworker 1 Phase, 230 Volt
IW60-3P208	60 Ton Ironworker 3 Phase, 208 Volt
IW60-3P230	60 Ton Ironworker 3 Phase, 230 Volt
IW60-3P380	60 Ton Ironworker Int'l - 3 Phase, 380 Volt, 50 Hz
IW60-3P460	60 Ton Ironworker 3 Phase, 460 Volt
IW60-3P575	60 Ton Ironworker 3 Phase, 575 Volt

60 TON WITH POWER LINK





60 TON ATTACHMENTS



OVERSIZE PLINCH ASSEMBLY

- · Accommodates punch & die sets in various shapes and
- Replaces Standard Punch Assembly or can be used as a secondary Punch Workstation

AC1024



- Accommodates punch & die sets in various shapes and sizes from 1" up to 4"
- Punch large holes and slots in anything from heavy sheet metal to steel beams

AC1055*



ANGLE NOTCHER

- Take precise 92° notch out of mild steel up to 3" x 3" x 1/4"
- · Allows for an easy 90° to create a steel frame

AC0125-1*



- Make clean 90° saddle joint connections quickly and easily
- Compatible with all Edwards Ironworkers
- Contact Edwards for custom
- dies to match your project Pipe Notcher Dies sold

separately

AC0925*



- Make clean 90° saddle joint connections quickly and easily
- Compatible with all Edwards Ironworkers
- Contact Edwards for custom dies to match your project
- Pipe Notcher Dies sold separately

AC0925T*



- Designed to shear flat bar up to 1/4" x 6" and angle iron up to 2" x 2" x 1/4"
- Shears solid round bar 1/4", 3/8", 1/2", 3/4" and 13/16" square bar

AC1075*



ROD SHEAR

- · Shear solid round rod easily with the Rod Shear
- Handles 1/4", 3/8", 1/2" 5/8" 3/4" and 1" solid

AC1074*



BRAKE WITH 4-WAY DIE

- Choose from the sizes listed below to meet your specific needs
- Fabricate brackets, frames, pans and tanks with this Brake with 4-Way Die

Includes a standard punch that allows 1/16", 1/8", 3/16" and 1/4" material to be formed to a 90° angle

AC1033*

AC1034*

60 TON ACCESSORIES



GAUGING TABLE KIT

- 3/8" thick 12" x 16" table that
- Compatible with both Standard and Oversize Pedestal Die Table
- Adjustable fences and handles quickly and easily guide your material for perfect repeatable actions

COPER NOTCHER GAUGING TABLE KIT

1/2" x 15-5/8" size table and

two fences to better align

vour material

vides a larger 3/8" x 12-



HEAVY DUTY GAUGING

- 1" x 12" x 16" table adds speed and precision to your Punch
- Replaces Standard Pedestal Die Table
- Adjustable fences and handles

STRIPPER REDUCING PLATE

distortion on thinner gauge

punches & dies set or smalle

materials when using 1/2"

Designed to minimize



HEAVY DUTY GAUGING TABLE KIT FOR OVERSIZED PUNCH ASSEMBLY

- 1" x 12" x 16" table adds speed and precision to your Punch Workstation
- Replaces installed Die Table Adjustable fences and handles

quickly and easily guide your material for perfect repeatable actions



URETHANE STRIPPER

 Minimize material distortion when working with light gauge material

AC1099



QUICK CHANGE PUNCH ASSEMBLY

- Accommodates punch and Increase your efficiency by saving time and money with the Quick Change Punch Assembly.
- Accepts both Standard and Oversize Punch & Die Sets

AC1001

AC0800



AUTO CUT - 48"

- Optimize your productivity or both the Flat Bar Shear and Angle Shear Workstations on your Edwards Ironworker
- The adjustable proximity sensor automatically cycles your Ironworker as you feed in material

AC1010

AC1914-3



BACK GAUGE - 48"

- Speed up production on repeatable cuts by providing an adjustable stop for the Flat Bar Shear and Angle Shear
- A positive stop attachment that is fitted to the back of the shearing

AC1011



PRESS BRAKE BACK GAUGE

- Speed up production providing an adjustable stop for the various size Brake Attachments
- A positive stop attachment that is fitted to the back of the Ironworker ensures accurate bending



PUNCH & DIE STARTER SET

- to accommodate the most commonly used bolts
- Sized in 1/8" increments fron 3/16" to 1-1/16" with 1/32" clearance See catalog page 68-71 for additional Punch & Die Sets



ACCESSORY LIGHT Super bright LED light with

M12 connections plugs Powerful magnetic base allows users to attach the

light to any Ironworker

surface and move as needed

AC1000



FABRICATOR'S PROTRACTOR

Increase user accuracy on

Workstations

Designed to guide your workpiece and gauged at 15° increments through 180°

AC1017



12" & 18" FENCES GUIDES

- Easily adjustable to align fence guides make precise.
- AC1910 12" Standard Handle AC1911 18" Standard Handles AC1912 12" Heavy Duty Handles AC1913 18" Heavy Duty Handles



PRODUCTIVITY PACK ocludes 5 Accessories designed

increase your accuracy and production speed. Accessory light

- 48" Auto Cut
- Fabricator's Protractor 3/8" x 12" x 16" Punch Station table Punch & Die Starter Kit



*IMAGE NOTE: Guarding removed for clarity